



DISTOR PIC

BALE SPIKE & STRAW SPREADER WITH VERTICAL ROTORS

The DISTOR PIC is a vertical rotor straw spreader equipped with a bale spike for handling bales and loading the machine. It's capable of processing both long and short strand round and square bales for bedding in cattle, farm & pig buildings. The machine is equipped with an overload protection system that ensure an even spread and prevents clumping and blockages, if material accumulates at the rotors, the bed chain slows down automatically to process the surplus of straw and regulate throughput. The DISTOR range is available with a rotor height of 0.9m or 1.2m.

Bale spike



Suitable for handling round and square bales, equipped with 2 tines of 130 cm Ø 40 mm. 90 cm spacing between tines.




Automatic hydraulic connection



Male connector located at the frame of the bale spike. Allows you to control all the hydraulic functions of the machine without having to exit the telehandler.

Spreading performance



Spreading is done by distribution of material:

- 180° Spreading
- Spreading width 6 m (up to 9m with optional deflector)

Unique straw spreading process



Vertical Rotors with spreading discs and superimposed projection trays to maximise efficiency and control the flow of straw.

STANDARD SPECIFICATION

- 2 spreading vertical rotors 0.9m / 1.2m
- Spreading Discs with projection trays
- Bale spike
- Cutting knives
- Manual side deflectors
- Overload protection
- Effort control adjusted bed chain speed and flow divider
- Automatic hydraulic connection
- Available with all common Telehandler brackets



A SELECTION OF OPTIONS



Cutting knives

Mounted directly onto the discs they improve performance when using large round bales or high-density bales.



2 Rotor heights

To adapt the machine according to the bales used – 0.9m or 1.2m.



Side deflectors

Adjustable manually (electric optional) they enable the width of spread to be adapted between 1.80 m to 6 m. A rear deflector is an option for achieving a spread of 9m.

Modèle	DISTOR PIC 90	DISTOR PIC 120
Square Bale 1,20 x 0,90 x 2,50 m	1	1
Square Bale 1,20 x 1,20 x 2,50 m	-	1
Round Bale	X	Ø 1,20 max.
Rotors design	8 discs & 6 retaining combs	10 discs & 8 retaining combs
Width of spreadin (m)	1,80 m to 9 m (with rear deflector)	
Overall height (mm)	1600	1900
Overall lenght (mm)	3950	
Overall width (mm)	2000	
Unloaded weight (kg)	1100	1550
Oil flow at the top of the boom (L/min)	45 - 50	
Min. Telehandler lift capacity (kg)	3000	3500

Head Office

22, Rue du Stade, 85130 La Verrie

T : +33 (0)2 51 65 41 36 // F : +33 (0)2 51 65 41 51

lucasg@lucasg.com // www.lucasg.com

YouTube : Lucas G

Facebook : LucasGFrance